

ALUMINUM FULL-VIEW DOORS

Clopay Models 905 and 906 are now available with a sleek panel design offering fewer lines and angles. The proportional rail and stile profiles, along with equal spacing, provide an aesthetically pleasing appearance. This sleek door is ideal in applications such as restaurants, auto dealerships and fire stations. In addition to these features, Models 905U and 906U feature Intellicore® polyurethane insulated rails and stiles while still maintaining the sleek look.



Section Joint Seal





Reinforcing Fin (where applicable)

clopaycommercial.com

OPTIONS PANEL OPTIONS AND CONFIGURATIONS

Aluminum Full-View Panel

Fewer panels than traditional aluminum doors allowing for a cleaner look.

Up to 9'0" Wide

1 Panel

MODELS 906 AND 906U - 7'6" TO 8'5" HIGH DOORS

9'1" to 17'2" Wide

CUSTOM PAINT OPTIONS Color Blast® finish paint system or RAL Powder Coating

PERFORMANCE OPTIONS

give you thousands of color options for endless

upgrades. See your Clopay Dealer for details.

COLOR BLAST

RAL Powder Coat finish.

Models 905U and 906U not available with

HEAVY-DUTY HARDWARE

2 Panel



FRAME COLOR OPTIONS



905/905U GLASS OPTIONS

906/906U GLASS OPTIONS

Gray Tinted

Tempered Glass

White Laminate

Glass

22'2" (905, 906) 20'2" (905U, 906U)

4.5" wide single up to 14'2"

6.5" wide double over 14'2"

Recessed panel with smooth surface

6063-T5 extruded aluminum alloy

Low-E glass

16'0"

2-1/8"

Full-view

Full-view

STANDARD SPECIFICATIONS

options available.



Clear Tempered Glass

Clear Laminate

Glass

Black Laminate

Glass

Max Width Max Height

Insulation

Emboss

Panel Style

Window Style

Exterior/Interior

Panel Thickness

End Stile Thickness

Section Construction



Bronze Tinted

Tempered Glass

Gray Laminate

Glass

Hardcoated acrylic options available.

Tempered Mirrored

Glass

Bronze Laminate

Glass



Double-end Hinge

SPECIALTY PRODUCTS



Exhaust Port

WINDCODE®





Glass	905/905U – Acrylic 906/906U – Tempered and laminate glass Tempered glass thicknesses of 1/8", 1/4" and 1/2" Acrylic thickness of 1/8" Laminate glass thickness of 1/4"	
Wind Load	Non-impact rated	
Joint Seal	Yes	
Springs	10,000 cycle springs Galvanized aircraft cable with minimum	7:1 safety factor
Tracks	2" angle mount track with standard lift 3" track where applicable	
Hardware	TPE astragal in corrosion-resistant retainer Steel step plate and lift handle Inside slide lock for increased security	Commercial 10-ball steel rollers 11 gauge hinges
Warranty	Standard Paint – 5 Years Material and Workmanship – 1 Year	Color Blast® finish – 5 Years Hardware – 1 Year



MADE IN USA

For more information on these and other Clopay products, visit clopaycommercial.com. Architects and specifiers, visit architectdoorhelp.com.

Intellicore® polyurethane (Models 905U and 906U)













17'3" to 22'2" Wide

3 Panel